



KNC/2019/

Date: 23.12.2019

REVISED QUOTATION NOTICE

Sealed quotation are invited under two bid system (technical + financial) for the following **renovation work of toilet block of Library building area of the College**. The details of the same are, as under:-

Renovation of Library Toilets at Kamala Nehru College, August kranti Marg, New Delhi					
S.No.	REF.OF DSR-2018	DESCRIPTION OF ITEMS	QUANTITY	UNIT	AMOUNT
1	14.82	Dismantling W.C. Pan of all sizes including disposal of dismantled materials i/c malba all complete as per directions of Engineer-in-Charge.	7.00	each	
2	15.52	Dismantling of flushing cistern of all types (C.I./PVC/Vitrious China) including stacking of useful materials near the site and disposal of unserviceable materials within 50 metres lead.	7.00	each	
3	15.20	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.			
3.1	15.2.1	Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix.)	1.70	cum	
3.2	15.2.2	Nominal concrete 1:4:8 or leaner mix (i/c equivalent design mix.)	2.55	cum	
4	15.23	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.			
4.1	15.23.1	For thickness of tiles 10 mm to 25 mm	175.00	sqm	
5	15.56	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	40.00	sqm	
6	17.2	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required :			
6.1	17.2.1	W.C. pan with ISI marked white solid plastic seat and lid	7.00	each	
7	17.31	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete.	5.00	each	
8	17.16A	Providing and fixing 8 mm dia C.P. / S.S. Jet with flexible tube upto 1 metre long with S.S. triangular plate to European type W.C. of quality and make as approved by Engineer - in - charge.	7.00	each	
9	17.34	Providing and fixing toilet paper holder :			
9.1	17.34.1	C.P. brass	7.00	each	
10	17.35	Providing and fixing soil, waste and vent pipes :			
10.1	17.35.1	100 mm dia			
10.2	17.35.1.2	Centrifugally cast (spun) iron socket & spigot (S&S) pipe as per IS: 3989	25.00	metre	

10.3	17.35.2	75 mm diameter :			
10.4	17.35.2.2	Centrifugally cast (spun) iron socketed pipe as per IS: 3989	35.00	metre	
11	17.36	Providing and filling the joints with spun yarn, cement slurry and cement mortar 1:2 (1 cement : 2 fine sand) in S.C.I./ C.I. Pipes :			
11.1	17.36.1	75 mm dia pipe	20.00	each	
11.1	17.36.2	100 mm dia pipe	15.00	each	
12	17.37	Providing and fixing M.S. holder-bat clamps of approved design to Sand Cast iron/cast iron (spun) pipe embedded in and including cement concrete blocks 10x10x10 cm of 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size), including cost of cutting holes and making good the walls etc. :			
12.1	17.37.1	For 100 mm dia pipe	20.00	each	
12.2	17.37.2	For 75 mm dia pipe	15.00	each	
13	17.38	Providing and fixing bend of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete.			
13.1	17.38.1	100 mm dia			
13.2	17.38.1.2	Sand cast iron S&S as per IS - 3989	10.00	each	
13.3	17.38.2	75 mm dia			
13.4	17.38.2.2	Sand cast iron S&S as per IS- 3989	10.00	each	
14	17.41	Providing and fixing double equal junction of required degree with access door, insertion rubber washer 3 mm thick, bolts and nuts complete :			
14.1	17.41.1	100x100x100x100 mm			
14.2	17.41.1.2	Sand cast iron S&S as per IS - 3989	5.00	each	
14.3	17.41.2	75x75x75x75 mm			
14.4	17.41.2.2	Sand cast iron S&S as per IS - 3989	5.00	each	
15	17.56	Providing and fixing terminal guard :			
15.1	17.56.1	100 mm			
15.2	17.56.1.2	Sand cast iron S&S as per IS - 3989	2.00	each	
15.3	17.56.2	75 mm			
15.4	17.56.2.2	Sand cast iron S&S as per IS - 3989	2.00	each	
16	17.60	Providing and fixing trap of self cleansing design with screwed downor hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floors			
16.1	17.60.1	100 mm inlet and 100 mm outlet			
16.2	17.60.1.1	Sand cast iron S&S as per IS: 3989	10.00	each	
17	18.8	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge.			

		Concealed work, including cutting chases and making good the walls etc.			
17.1	18.8.1	15 mm nominal outer dia Pipes	30.00	metre	
18	18.54	Providing and fixing PTMT bib cock of approved quality and colour.			
18.1	18.54.2	15 mm nominal bore, 122mm long, weighing not less than 99 gms	7.00	each	
19	18.55	Providing and fixing PTMT stop cock of approved quality and colour.			
19.1	18.55.1	15 mm nominal bore, 86 mm long, weighing not less than 88 gms	7.00	each	
20	18.58	Providing and fixing PTMT grating of approved quality and colour.			
20.1	18.58.1	Circular type			
20.2	18.58.1.1	100 mm nominal dia	10.00	each	
21	18.74	Providing and fixing unplasticised P.V.C. connection pipe with PTMT Nuts, collar and bush of approved quality and colour.			
21.1	18.74.1	15 mm nominal bore with 30cm length	12.00	each	
22	18.79	Making hole up to 20x20 cm and embedding pipes up to 150 mm diameter in masonry and filling with cement concrete 1:3:6 (1 cement : 3 coarse sand: 6 graded stone aggregate 20 mm nominal size) including disposal of malba.	10.00	each	
23	22.3	Providing and laying water proofing treatment to vertical and horizontal surfaces of depressed portions of W.C., kitchen and the like consisting of:			
23.1	(i)	Ist course of applying cement slurry @ 4.4 kg/sqm mixed with water proofing compound conforming to IS 2645 in recommended proportions including rounding off junction of vertical and horizontal surface.			
23.2	(ii)	IIInd course of 20 mm cement plaster 1:3 (1 cement : 3 coarse sand) mixed with water proofing compound in recommended proportion including rounding off junction of vertical and horizontal surface.			
23.3	(iii)	IIIrd course of applying blown or residual bitumen applied hot at 1.7 kg. per sqm of area.			
23.4	(iv)	IVth course of 400 micron thick PVC sheet. (Overlaps at joints of PVC sheet should be 100 mm wide and pasted to each other with bitumen @ 1.7 kg/sqm).	25.00	sqm	
24	4.2	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing:			
24.1	4.2.2	1:1½:3 (1 cement : 1½ coarse sand (zone-III) : 3 graded stone aggregate 20 mm nominal size).	5.00	cum	

	8.31				
25		Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	160.00	sqm	
26	11.39	Providing and laying rectified Glazed Ceramic floor tiles of size 300x300 mm or more (thickness to be specified by the manufacturer), of 1st quality conforming to IS : 15622, of approved make, in colours White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement: 4 Coarse sand), jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc., complete.	17.00	sqm	
27	14.1	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge.			
27.1	14.1.1	With cement mortar 1:4 (1 cement : 4 fine sand)	20.00	sqm	
28	13.44	Finishing walls with water proofing cement paint of required shade :			
28.1	13.44.1	New work (Two or more coats applied @ 3.84 kg/10 sqm)	50.00	sqm	
29	15.4	Dismantling C.I. or asbestos rain water pipe with fittings and clamps including stacking the material within 50 metres lead :			
29.1	15.42.1	75 to 80 mm dia pipe	10.00	metre	
29.2	15.42.2	100 mm dia pipe	10.00	metre	
30	17.7	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require:			
30.1	17.7.4	White Vitreous China Flat back wash basin size 550x400 mm with single 15 mm C.P. brass pillar tap	5.00	each	
31		Serial no 31 (REMOVED)because it was same as Serial no 8			
32	15.6	Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	5.00	cum	
	TOTAL				
		Add Contingency charges 5%			
		Total			

Terms & Conditions:-

1. The rates should be included all the taxes/GST/Freight etc.
2. Payment will be mad by RTGS/NEFT within 15 days after completion of work. All payment will be subject to deduction of taxes at source as per applicable rules.
3. The bidders are strictly required to attach a copy of GST/VAT registration certificate of the firm, with PAN number of the firm/ owner otherwise bid/quotation will be deemed rejected.
4. In complete/conditional quotation will not be accepted.
5. On inspection, if the material or workman is not found as per the specifications or any item is found damaged the same shall be rejected. In case of rejection of the materials, no payment will be made for the rejection item.
6. In the event of any dispute, arising between the parties hereafter referred as Kamala Nehru College and Supplier/Dealer in respect of or connected with this quotation in all such matters the venue of proceedings will be Delhi and only Delhi or appropriate Courts will have jurisdiction over the same.

Please submit all the information in separately sealed envelopes (**GST paper & required papers must be attached**) through **Registered/Speed post/Courier only (by hand submission will not be accepted)**, and send to this office addressed to the Principal, Kamala Nehru College, August Kranti Marg, New Delhi-110049, with full address and written on the top of the envelope, **Quotation for renovation work of toilet block of Library building area of the College**, respectively. The amount must be mentioned in words & figures both and the quotation in a sealed enveloped received in this office latest by 3 weeks from the date of publication upto 4:00 p.m. The Principal reserves the right to reject/accept any or all quotation without assigning any reason thereof.

Yours sincerely,



Dr. Kalpana Bhakuni
Principal (Officiating)